

The 23 mm Round with Armour-Piercing Incendiary Tracer Projectile is intended to engage air and ground targets.

The ammunition is safe in transport, storage and handling and ensures the reliable performance of the gun systems in all weather conditions.

The ammunition is designed for use with guns 2A14, 2A14M, 2A7 and 2A7M of the following 23 mm air-defence gun mounts and their modifications:

- ZU-23-2
- ZSU-23-4 SHILKA.



BASIC CHARACTERISTICS

Caliber:	23 x 152 mm
Armour penetration (at angle of hit 30° and range of 1200 m):	10 mm armour plate
Operational Temperature Range:	-50 to +50°C
Shelf Life:	15 years

PACKING

84 rounds in three air-tight sealed metal boxes in a wooden case with dimensions:	875 x 378 x 206 mm.
Gross weight:	55 kg.
Volume:	0.068 cu. m.

ELEMENTS OF ROUND

Projectile:	Armour-Piercing Incendiary Tracer
Incendiary Composition:	DU-5
Propellant:	5/7 Cfl
Cartridge Case:	steel
Percussion Primer:	KV-3

BALLISTIC DATA

Muzzle Velocity:	955 – 985 m/s
Average Pmax:	2925 kgf/cm ²
Maximum range:	2500 m
Maximum altitude:	1500 m

TECHNICAL DATA

Weight of Round:	450 g
Length of Round:	235 mm
Weight of Projectile:	190 g
Length of Projectile:	99.3 mm
Weight of cartridge case:	172 g
Length of cartridge case:	151.5 mm
Propellant Charge Mass:	76 g

CONTACTS