



Specifications	14.5x114 MM API	14.5x114 MM API-T
Caliber	14.5mm	
Muzzle velocity	987.5± 7.5m/s	1005± 10 m/s
Max. Chamber pressure(average)	≤319Mpa	≤319Mpa
Weight of Bullet	175g-191g	189g-200g
Length	154.5-156mm	154.5-156mm
Length of case	113.6-114mm	113.6-114mm
Weight of bullet	62.6g-64.6g	60.5g-63g
Material of bullet	Steel core, steel jacket and gilding metal envelope	
Material case	Steel	
Primer	Berdan Primer	
Propellant Powder	Graphite single Base	

Penetration performance API: Armor-piercing Rate>80% (Pierce 20 mm steel plate at 200m in 20 ° AOI) Incendary Rate>80% (Pierce 20 mm steel tank and ignite the fuel at 100m in 20 ° AOI)

Penetration performance API-T: Armor-piercing Rate>80% (Pierce 20 mm thicl steel plate at 200m in 20 °) Incendary Rate>80% (Pierce 20 mm steel tank and ignite the fuel at 100m in 20 ° AOI)
Tracer Rate >80% (2000m)

Suitable Weapon : 14.5 mm quadruple AAMG , 14.5 mm twin-barreled AAMG ,14.5mm AAMG